

RE A DUAL BOILER FULLY SATURATED DUAL BOILER MACHINE

GROUPS	2	3	4
TECHNOLOGY	Dual Boiler	Dual Boiler	Dual Boiler
PORTION CONTROL	Automatic	Automatic	Automatic
COFFEE BOILER	4 l	6.3 l	8.5 l
MAIN BOILER	9 l	12 l	18 l
POWER	5.15 KW	5.95 KW	7.46 KW
WIDTH (mm)	760	980	1,200
DEPTH (mm)	585	585	585
HEIGHT (mm)	491	491	491
BODYWORK	Stainless steel AISI 304 (black or white by request)		
BOILER MATERIAL	Stainless steel AISI 304		
THERMAL CONTROL	PID / Pressure transducer		
STEAM WANDS	Stainless steel + cool touch		
CUPS HEIGHT	86 mm / 123 mm (ALTO version by request)		
SHOT TIMER	Standard		



RE A TIMER THERMO SIPHON HEAT EXCHANGE MACHINE

GROUPS	2	3	4
TECHNOLOGY	Thermosiphon	Thermosiphon	Thermosiphon
PORTION CONTROL	Automatic	Automatic	Automatic
BOILER	14.5 l	23.0 l	28.0 l
POWER*	4.3 KW	5.3 KW	6.3 KW
WIDTH (mm)	760	980	1,200
DEPTH (mm)	585	585	585
HEIGHT (mm)	491	491	491
BODYWORK	Stainless steel AISI 304 (black or white by request)		
BOILER MATERIAL	Copper		
THERMAL CONTROL	Pressure transducer		
STEAM WANDS	Stainless steel + cool touch		
CUPS HEIGHT	86 mm / 123 mm (ALTO version by request)		
SHOT TIMER	Standard		

*Special power ratings available by request

